


Waveguide Termination

WR15 (BJ620) Waveguide Matched Termination, ME-WT-WR15 49.8-75.8 GHz, 0.5 W, FUGP620 Flange, Round

QR code



Hangzhou Multipath Electronics Co., Ltd., Zhejiang, China

⚙️ Electrical & Environmental


Frequency Range	49.8 - 75.8 GHz	Impedance	50 ohm
VSWR	1.04 max	Input Avg Power	0.5 W @ 25 °C

⚙️ Mechanical & Product Information


Product Number	ME-WT-WR15, H-Grade	Waveguide	WR15 (BJ620), FUGP620 Flange
Waveguide Body	Copper, gold plated	Waveguide Cavity	Copper, gold plated
Heat Sink	N/A	Net Weight	About 22.2 g
Operating Temp	-55 °C~+100 °C		

Outline dimensions

Dimensions(mm) Tolerance $\pm 1\%$




Typical Test Data



Customized connectors, dimensions, PIM, VSWR.

Notes: To ensure longevity and performance, do not use at full power for a long time. Peak power, pulse width, and dutycycle need to meet therequirements. Input high power, require heat dissipation, maintain temperature within 60°C. Reference Curve,deratelinearlyto 0.1W at 100°C.



Multipath Electronics

Contact

+86-571-56201039

sales@multipath.cn

<https://www.multipath-electron.com>

Technical specifications in this datasheet are subject to change without notice. Actual products may differ from the shown images.